

SpeedTouch™ 536(i) v6

Multi-User ADSL2+ Gateway



SpeedTouch 536(i) v6

Versatility Made Simple

The SpeedTouch 536(i) provides unmatched peace-of-mind to operators looking to deploy a simple and flexible ADSL gateway without making any compromise on performance and security.

USB or Ethernet ports can be used to connect to the gateway, offering an interface for virtually any device –computer or game console– accessing the Internet.

It also offers a fast, full-feature routing engine as well as a solid firewall to ensure the best end-user experience.

Easy installation

With the SpeedTouch 536(i), a new standard in user-friendliness has been set. When the installation process is started the end-user is only five clicks away from surfing the web. After connecting PC, laptop, or local area network to the modem over the Ethernet or USB interface, the advanced Setup Wizard will guide the end-user through the installation process.

The Setup Wizard is easily customizable to the look-and-feel and the network parameters of the service provider, offering a seamless end-user experience to their customers.

Home networking

This gateway is the ideal solution for residential and SOHO users where there is an urgent need to share ADSL access with other family members or colleagues. Residential users will especially appreciate the fact that PCs, game consoles, PDAs, set top boxes, and other devices can instantly connect to the Internet through a single high-speed ADSL point of access.

Security

This ADSL residential gateway has a built-in firewall that denies unauthorized access to all PCs and Internet devices hooked up to the user's broadband ADSL connection. The SpeedTouch 536(i)'s powerful firewall can be configured by end-users, equipment retailers or service providers for a broad range of security policies and requirements. Attacks are stopped in the gateway and will not reach the networked devices. With the SpeedTouch 536(i), you'll be secure 24/7.

SpeedTouch™ 536(i) v6

Multi-User ADSL2+ gateway



Technical summary

▶ Hardware specifications

- Interfaces:
 - LAN:
 - 10/100Base-T (RJ45)
 - MDI/MDI-x autosensing
 - 1 Ethernet port and 1 USB port
 - WAN:
 - ADSL line (RJ11) for ADSL/POTS or ADSL/ISDN
- Dimensions: 30 X 147 X 114mm (1.18 x 5.78 x 4.48 in.)
- Temperature: 0°to 40°C (32 to 105 F)
- Humidity: 20% to 80%
- AC voltage: 100 to 120, 220 to 240 V
- Frequency: 50/60 Hz

▶ ADSL modem specifications

- ADSL: G.hs, ANSI, ETSI, G.dmt, G.lite, Annex A, B
- ADSL2: G.dmt2, G.lite2, Annex A, B, L
- ADSL2+: G.dmt2+, Annex A, B, L

▶ Multi-user Router

- ATM-Extensive multi PVC
 - ATM Quality of Service (UBR, CBR, VBR-rt, VBR-nrt)
 - DSLForum TR-37 autoconfiguration
- Bridging-self learning bridge at wire speed
- IP Routing
 - UPnP* certified Internet Gateway Device, enabling major conferencing and gaming technologies
 - IPsec passthrough from multiple LAN clients, enabling secure homeworking
 - Supports PPPoE, PPPoA, IPoA, CIP, ETHoA-DNS server and relay, DHCP server and relay
 - Network Address Translation for connection sharing, including support for SIP, H.323, Realaudio, ftp, irc, IKE, IPsec-ESP, Jabber, ILS,...
 - Simultaneous bridging and routing of PPPoE connections, enabling network based VPN's

▶ Management

- OS independent on the Ethernet interface
- Easy set-up wizard
- Advanced Management via telnet, HTTP, SNMP, event log
- Integrated firewall
- Easy SW upgrade wizard

▶ USB drivers

- Host software support for:
 - Windows 98, 98SE, 2000, ME and XP
 - Mac OS9, OSX,
- Plug-and-play installation
- Simple software upgrade procedure
- USB integrated as virtual Ethernet on PC

▶ Content of the box

- SpeedTouch 536 or 536i
- Ethernet cable (RJ45)
- Telephone cable (RJ11)
- USB cable
- Cable filter (optional)
- Power adapter
- Quick installation guide
- SpeedTouch set-up CD-ROM

* UPnP™ is a certification mark of the UPnP™ Implementers Corporation



SpeedTouch 536(i) v6

▶ For more information: www.speedtouch.com

All rights reserved ©2005, Thomson.

Printed in EU. 536v6_ed01

All trademarks are owned by their respective owners.

Product specifications subject to change without prior notice.